


JOB #:

ITEM #:

QUANTITY:

MOUNTING	HANDING	TYPE	SIZE	OTHER



SPECIFICATIONS

Body: Fabricated of #22 ga stainless steel. 2 1/2" space above and below door allows for air circulation.

Flange: Fabricated of #22 ga stainless steel with #4 satin finish and 1/4" returns to wall, no miters or welds.

Cabinet Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet body.

Cabinet Door: Fabricated of #22 ga stainless steel with #4 satin finish secured by means of magnetic catches with door knob or easy opening.

Lower Shelf: Lower shelf is #22 ga stainless steel finished to match body with front edge rolled to prevent injury.

Upper Shelf: Stainless steel shelf welded in place for storage.

Retaining Rod: Stainless steel rod across the width of the cabinet prevents bed pan from falling out when doors are opened.

Hinge: Heavy duty, full length, stainless steel piano type hinge.

Collars: Fabricated of #22 ga #4 satin finish stainless steel finished to match cabinet body.

Overall Size: 17 1/4"W x 27 1/4"H x 6 1/4"D
438mm x 692mm x 159mm

Wall Opening: 15 3/4"W x 25 3/4"H x 6"D
400mm x 654mm x 152m

U951-S2: 2" semi-recessed with 4 1/4" wall opening

U951-S4: 4" semi-recessed with 2 1/4" wall opening

U951-SM: Fully surface mounted

INSTALLATION

Coordinate installation with contractor and architect to avoid interference with pipes vents etc. Provide a rough wall opening 15 3/4"W x 25 3/4"H. Wall opening depth will depend on style mounting. If a collar is required, slip over back of unit. Open door & install unit in opening. Make sure cabinet will sit flush in wall and secure with proper fasteners per application.

NOTES