

509 Temple Hill Road New Windsor, NY 12553-5532 **P.** (845) 562-3332 | **F.** (845) 562-3391

LOW PROFILE AUTOMATIC HAND DRYER







FEATURES

- Universal voltage
- Low profile design
- Suitable for light traffic areas
- Operates automatically using infrared sensor
- Dual output for maximum efficiency
- Thermal protection system prevents dryer from overheating
- ADA Compliant





LOW PROFILE AUTOMATIC HAND DRYER

SPECIFICATIONS

Operating Voltage: Universal Voltage, 100-240VAC, 50/60 HZ, 2.3kW

Warm Air Speed Output: 60.2 mph (27 m/s)

Air Output Temperature: ~135°F (57°C) – Ambient Temp. 68°F (20°C)

Air Output Volume: 220 CFM (374,000 m³/h)

Motor Type: .1hp, 350-700W, 7500 RPM, brushed

Motor Thermal Protection: Auto resetting thermostat turns unit off at 201°F (94°C)

Heater Element: Two (2) 1kW heating elements

Heater Thermal Protection: Auto resetting thermostat turns unit off at 266°F (130°C)

Drying Time: ~25 seconds

Sensor Range: 2" to 6" (51mm to 152mm), adjustable;

Timing Protection: 45 second auto shut off Cover: One piece formed steel, painted white

Warranty: 2 year limited warranty Shipping Weight: 12 lbs. (5.4kg)

Unit Size: 13"W x 10"H x 4"D (355mm x 254mm x 101.6mm)

MOUNTING HEIGHTS

Dryer Application	Height
Men	43" (117cm)
Women	41" (112cm)
Children (ages 11-17)	39" (112cm)
Children (ages 3-10)	33" (81 cm)
ADA Compliance	35" (94cm)





To ensure proper function, Hand dryer must be installed by qualified licensed electrician



