

## **UJ9 Series** Single Robe Hook Strip

JOB #:
ITEM #:
OLIANTITY:

Revision 1/14

	Products	Revisi	on 1/14	QUANTITY:	
OUNTING	HANDING	TYPE SIZE	OTHER	₹	
		Length			2 1/8"
					54mm1/2"
					13mm
Width				]	
				_	_
PECIFICATIONS			INSTALLATION		
ak Ciria, Eshrisata - 1-1	#18 ga stainless steel	20 04 0 6 1 1			
or strip: rapricated of	or maximum rigidity	with a #4 satin finish and	Place unit to wall surface	ce making sure unit is leve	el and transfer
ooks: UX110-SF satin f	nish stainless steel ho	with a #4 satin finish and oks (to match strip) with	Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
	nish stainless steel ho		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve illot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rrify Style: 19A: 16"L (610mm) with	nish stainless steel hors welded to hook strip. 3 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve illot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve illot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve illot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style:  9A: 16"L (610mm) with 9B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style:  9A: 16"L (610mm) with 9B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		Place unit to wall surface mounting points. Drill p per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style: 19A: 16"L (610mm) with 19B: 26"L (914mm) with	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene
ooks: UX110-SF satin fincealed mounting plates rify Style:	nish stainless steel ho s welded to hook strip. 3 hooks 4 hooks		per application.	ce making sure unit is leve ilot holes and secure unit	el and transfer with proper fastene