

U449 Waste Receptacle

Revision 03/11

	JOB #:
	ITEM #:
	QUANTITY:

ıS

MOUNTING **HANDING** TYPE SIZE OTHER 14 1/4" 6 1/4" 362 mm 6 1/4" 159 mm 1/4" 12 1/4" 159 mm 1/4" 311 mm 6 mm 6 mm 48' 1219 mm -S4 4" 102 mm 40" <u>-S2</u> 2" 51 mm 1016 mm

INSTALLATION **SPECIFICATIONS**

Removable

Extended Waste

Body: Fabricated of #22 gauge stainless steel with #4 satin finish on all exposed areas.

₽S

Door: Fabricated of #22 gauge, one piece stainless steel secured to body by means of a full length heavy duty stainless steel piano type hinge.

Flange: Fabricated of #22 gauge stainless steel finished to match cabinet. One piece construction without miters or welds with 1/4" returns to wall.

Removable Waste: Heavy duty pre-plated steel with large service handle for easy servicing.

Back: Fabricated of stainless steel formed for rigidity with multiple welds to cabinet.

Locks: Pin tumbler commercial quality type, keyed like all other AJW

Collars: #22 gauge stainless steel sized and finished to match cabinet, surf mount & semi-recessed.

Overall Size: 14 1/4"W x 48"H x 6 1/4"D

362mm x 1219mm x 159mm

(3)

Wall Opening: 12 3/4"W x 46 1/2"H x 6"D

324mm x 1181mm x 152mm

U449-S2: 2" semi-recessed. Collar with 4" (102mm) wall opening U449-S4: 4" semi-recessed. Collar with 2" (51mm) wall opening

U449-SM: Surface Mounted Capacity: 10.5 gallons (1.4 cu ft)

Options:

-P: Rigid Plastic Waste

Coordinate installation with architect and contractor. Provide a wall opening 12 3/4"W x 46 1/2"H. Wall depth will vary will vary if collars are required. Open bottom door and remove waste from cabinet and insert in wall opening. Secure unit with proper fasteners per each application. Make sure unit is plumb. After unit has been secured, place waste back into cabinet and secure door.

-SM

NOTES